

# CASES 1150 Case



## 1150 Case

- **Watertight, crushproof, and dust proof**
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Unconditional Lifetime Guarantee of Excellence

## 1150 Case Configurations

Cat. #	Description
1150	1150 Case
1150NF	1150 Case (No foam)



Black



Silver



Orange



Yellow



Blue



OD Green\*



Desert Tan\*

\*Desert Tan & OD Green available Special Order

## 1150 Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
9.12" x 7.56" x 4.37" (23.2 x 19.2 x 11.1 cm)	8.18" x 5.68" x 3.62" (20.8 x 14.4 x 9.2 cm)	
Lid Depth	Bottom Depth	Total Depth
0.75" (1.9 cm)	2.87" (7.3 cm)	3.62" (9.2 cm)
Weight w/Foam	Weight w/o Foam	Buoyancy Max.
1.98 lbs. (0.9 kg)	1.76 lbs. (0.8 kg)	8 lbs. (3.63 kg)
Range Temperature		
-10 / 210° F (-23 / 99° C)		

## 1150 Case Certificates

- IP67 • STANAG 4280

## 1150 Case Accessories

Cat. #	Description
1150PF	Special Application Panel Frame
1151	3 pc. Replacement Foam Set
1153	Replacement O-ring

Authorized Distributor: **Custom Case Company**  
 2526 Leitrim Rd., Ottawa ON K1T 3V3 Tel: (613)-822-0620 Fax: (613)-248-4731  
 e-mail: [info@customcaseco.com](mailto:info@customcaseco.com) Website: [www.customcaseco.com](http://www.customcaseco.com)