



iM2450 Storm Case



- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Vortex® Valve
- Flush Powerful Hinges
- Meets Carry-on Regulations
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2450 Storm Case Configurations

Cat. #	Description
iM2450	iM2450 Storm Case
iM2450-X0000	iM2450 Storm Case (No foam)
iM2450-X0002	iM2450 Storm Case with Padded Dividers



Black



OD Green

iM2450 Storm Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
19.20" x 15.20" x 9.00" (48.7 x 38.6 x 22.9 cm)	18.00" x 13.00" x 8.40" (45.7 x 33 x 21.3 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	7.00" (17.8 cm)	9.00" (22.9 cm)
Weight with foam	Weight without foam	Buoyancy Max.
8.9 lbs. (4.04 kg)	7.4 lbs. (3.36 kg)	63.62 lbs. (28.86 kg)
Range Temperature		
-20 / 140° F (-29 / 60° C)		

iM2450 Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2450 Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-STRAP-S-VER2	Padded Shoulder Strap
iM-VALVE-M-B	Manual Purge Valve
iM2450-DIV	Padded Dividers
iM2450-FOAM	Replacement Foam
iM24XX-BEZEL	Base Bezel Kit
iM24XX-BEZEL-LID	Lid Bezel Kit
iM24XX-PHOTOPALLET	Photography Pallet
iM24XX-UTILITYORG	Utility Organizer