

CASES
iM2950
 Pelican Storm Case



iM2950 Storm Case



- Five Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2950 Storm Case Configurations

Cat. #	Description
iM2950	iM2950 Storm Case
iM2950-X0000	iM2950 Storm Case (No foam)
iM2950-X0002	iM2950 Storm Case with Padded Dividers



Black



Yellow



OD Green

iM2950 Storm Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
31.30" x 20.40" x 12.20" (79.5 x 51.8 x 31 cm)	29.00" x 18.00" x 10.50" (73.6 x 45.7 x 26.7 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	8.50" (21.6 cm)	10.50" (26.7 cm)
Weight with foam	Weight without foam	Buoyancy Max.
28.7 lbs. (13.02 kg)	20.8 lbs. (9.43 kg)	260.65 lbs. (118.23 kg)
Range Temperature	No. of Wheels	Retractable Handle
-20 / 140° F (-29 / 60° C)	2	YES

iM2950 Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2950 Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-VALVE-M-B	Manual Purge Valve
iM2950-DIV	Padded Dividers
iM2950-FOAM	Replacement Foam
iM29XX-BEZEL	Base Bezel Kit
iM29XX-BEZEL-LID	Lid Bezel Kit
iM29XX-UTILITYORG	Utility Organizer